

Technical specifications




flotex[®] classic

Flotex classic meets the requirements of EN 1307

| | | | |
|---|--------------------------|-------------------------------|--------------------------------|
|  | Total thickness | EN-ISO 1765 | 4.3 mm |
|  | Roll width | EN-ISO 24341 | 200 cm |
|  | Roll length | EN-ISO 24341 | 30 m |
|  | Total weight | ISO 8543 | 1800 gram/m ² |
| | Pile installation weight | ISO 8543 | Approx 250 gram/m ² |
| | Pile thickness | ISO 1766 | Approx 2 mm |
| | Pile material | | 100% polyamide |
|  | Dimensional stability | EN-ISO 23999 | ≤ 0.2% |
|  | Light fastness | EN ISO 105/B02 | ≥ 6 |
|  | Resistance to chemicals | EN-ISO 26787 | Very good |
|  | Contact sound insulation | ISO 140-8 | ΔLw = 20 dB |
|  | Slip resistance | DIN 51130 / 51131 EN 13893 | R13 DS: > 0.30 |

Flotex meets the requirements of EN 14041



| | | | |
|---|----------------------|-----------------------|--------------------------|
|  | Fire resistance | ECE-R 118 / FMVSS 302 | Approved |
|  | Body voltage | ISO 6356 | < 2 kV |
|  | Thermal conductivity | EN 12524 | 0.048 m ² K/W |

All countries

Forbo Flooring Systems
High Holborn Road
Ripley
Derbyshire DE5 3NT
UK

Tel: +44 (0) 1773 744121
Fax: +44 (0) 1773 744142

Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England: 9200318