










# Technical specifications

**flotex**<sup>®</sup> FR

Flotex FR meets the requirements of EN 1307

	Total thickness	ISO 1765	Approx 3.3 mm
	Roll width	EN-ISO 24341	200 cm
	Roll length	EN-ISO 24341	30 m
	Light fastness	EN-ISO 105/B02	6
	Pile material		100% polyamide
	Dimensional stability	ISO 2551	≤ 0.20%
	Total weight	ISO 8543	Approx 1225 gram/m <sup>2</sup>
	Pile installation weight	ISO 8543	Approx. 250 gram/m <sup>2</sup>
	Pile thickness	ISO 1766	Approx 2 mm
	Electrical resistance	EN 10965	Approx. 10 <sup>10</sup> Ω
	Contact sound insulation	ISO 140-8	Δ Lw = approx. 22 dB

Flotex FR product meets the demands set by EN 14041



	Slip resistance	EN 13893	> 0.30
	Body voltage	ISO 6356	< 2 kV

## EC declaration of conformity

IMO Resolution A653(16)

IMO Resolution MSC 307(88) Annex 1 Part 2

IMO Resolution MSC 307(88) Annex 1 Part 5

US Coast Guard approval ref: 164.117/1121/WCL MED0364

### All countries

Forbo Flooring Systems  
High Holborn Road  
Ripley  
Derbyshire DE5 3NT  
UK  
Tel: +44 (0) 1773 744121  
Fax: +44 (0) 1773 744142  
Email: [info@forbo-transportflooring.com](mailto:info@forbo-transportflooring.com)  
[www.forbo-flooring/transportation](http://www.forbo-flooring/transportation)

### Registered Office:

Forbo Flooring UK Limited  
High Holborn Road, Ripley  
Derbyshire DE5 3NT  
Registered in England: 9200318