



















tessera[®] acrobat

Acrobat carpet tiles meet the requirements of EN 1307

	Description	Cut pile carpet tile
	Dimensions	50cm x 50cm
	Total thickness	8.0mm ± 10%
	Pile height	5.0mm ± 0.5mm
	Collection size	32 colourways 5m ² per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Antron [®] polyamide 6.6
	Dye method	100% piece dyed
	Stitch density	181,102 per m ² ± 10%
	Pile weight	1,050 gsm ± 10%
	Total weight	4,650 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	Modified bitumen and polyester fleece
	Castor chair use	EN 985 Minimum R value: ≥2.4
	Light fastness	EN ISO 105 B02 ≥5
	Dimensional stability	EN 986 ≤0.2%
	Creating Better Environments	
	Indoor Air Quality	Acrobat meets 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	CRUK	Forbo Flooring UK Ltd is a member of Carpet Recycling UK
	Guarantee	Acrobat carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Broadloom, quarter turn or tessellated

Acrobat carpet tiles meet the requirements of EN 14041



	Reaction to fire	EN 13501-1:	B _{f1} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV)

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

Forbo Flooring Systems reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

Forbo Flooring
 't Hofveld 4
 1702 Groot-Bijgaarden
 Tel: +32 2 464 10 10
 Fax: +32 2 464 10 11
 info.belgium@forbo.com
www.forbo-flooring.be